

# HPE Aruba Networking CX 6200 Switch Series

HPE Aruba Networking CX 6200M 36G 12SR5 Class6 PoE 4SFP+ Switch (R8Q71A)



## What's new

- Enterprise-class connectivity with support for ACLs, robust QoS, and common protocols such as static and Access OSPF routing.
- Up to 384 ports of scalability with 8-member VSF stacking. 24 and 48-port fixed and modular switches can stack together with easy to deploy through the CX Mobile app.
- Models include modular switches with 1/10

## Overview

The HPE Aruba Networking CX 6200 Switch Series is a next-gen family of stackable access switches ideal for enterprise branch offices, campuses, and SMB networks. With a cloud-centric design that combines a fully programmable OS with the HPE Aruba Networking CX Network Analytics Engine, this switch family extends industry-leading deployment, monitoring, and troubleshooting to the access layer.

Make your network ready for tomorrow's unpredictable demands with a powerful Gen7 ASIC architecture to deliver fast, non-blocking performance. HPE Aruba Networking Virtual Stacking Framework (VSF) allows for stacking of up to 8 switches, providing scale and simplified

GbE uplinks, LRM, and MACSec 256, fixed switches with either 1/10 GbE SFP+ or 1 GbE SFP uplinks, and options that support 30W to 60W of PoE per port.

- Intelligent monitoring and visibility via HPE Aruba Networking CX Network Analytics Engine. HPE Aruba Networking Switch Multi-Edit Software support for automation, configuration and verification.
- Dynamic Segmentation enables secure access for users and IoT.
- Flexible, modular switch models support hot-swappable, redundant power supplies and fans for enhanced resiliency.

management. This series includes fixed (CX 6200F) and modular (CX 6200M) switches with built-in high speed uplinks and up to 1440W of PoE to support IoT devices such as security cameras and wireless APs.

## Features

### Performance and Power at the Edge

The HPE Aruba Networking CX 6200 Switch Series provides Layer 3 access switching with high performance, security, and ease of use for enterprise edge, SMB, and branch office networks.

A fully distributed architecture with Gen7 ASICs deliver very low latency, increased packet buffering, and adaptive power consumption. Switching and routing are wire-speed to meet the demands of bandwidth-intensive workloads.

HPE Aruba Networking Virtual Switching Framework (VSF) allows you to quickly grow your network using high performance front-plane stacking. Create 8 member stacks using built-in SFP+ ports with flexibility to create stacks that span longer distances using long-range transceivers.

Deploy wireless access points and IoT devices with HPE Aruba Networking CX 6200 models that support up to 1440W IEEE 802.3at Class 6 Power over Ethernet for up to 60W per port.

Flexible, modular switch models support hot-swappable, redundant power supplies and fans for enhanced resiliency.

### Automation and Analytics

The HPE Aruba Networking CX 6200 Switch Series delivers visibility and built-in analytics for real-time monitoring and accelerated troubleshooting. The HPE Aruba Networking CX Network Analytics Engine (NAE) automatically interrogates and analyzes events that can impact network health.

Advanced telemetry and automation provide the ability to easily identify and troubleshoot network, system, application, and security related issues easily through the use of Python agents and REST APIs.

The Time Series Database (TSDB) stores configuration and operational state data, making it available to quickly resolve network issues.

HPE Aruba Networking Switch Multi-Edit Software introduces automation that allows for rapid network-wide changes, and ensures policy conformance post network updates. Intelligent capabilities include search, edit, validation (including conformance checking), deployment, and audit features.

The HPE Aruba Networking CX Mobile App simplifies connecting and stacking this switch series with easy one touch deployment. Import switch information into HPE Aruba Networking Switch Multi-Edit Software for simplified configuration management and to continual conformance validation.

### Simplified Configuration and Management

The HPE Aruba Networking CX 6200 Switch Series provides flexibility to manage and simplify configurations with HPE Aruba Networking Central, HPE Aruba Networking Switch Multi-Edit Software, easy to use web GUI, or industry standard CLI.

HPE Aruba Networking Switch Multi-Edit Software introduces automation that allows for rapid network-wide changes and verifies policy conformance post network updates.

Unified management across wired, wireless, and WAN using HPE Aruba Networking Central.

Reduce manual IT operation tasks around initial deployment or on-going configuration changes to accommodate adds, moves, and changes with colorless ports using local user roles and local-MAC-Authentication (LMA).

Ready for software-defined networking with REST APIs for fine-grained programmability of network tasks.



**Smarter Segmentation**

The HPE Aruba Networking CX 6200 Switch Series supports Dynamic Segmentation that automatically applies and enforces common and consistent user, device, and application-aware policies on HPE Aruba Networking wired and wireless networks.

Automated device profiling, role-based access control, and Layer 7 firewall features deliver enhanced visibility and performance for a better overall experience for IT and end-users.

Switch-to-switch tunnels with VXLAN for low-latency and high performance use cases.

Reduces time-consuming and error-prone task of adds, moves and changes.



Technical specifications

HPE Aruba Networking CX 6200M 36G 12SR5 Class6 PoE 4SFP+ Switch

|                            |                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Number             | R8Q71A                                                                                                                                                                                                                                                                                                                                                                               |
| Differentiator             | 36x ports 10/100/1000BASE-T Class 6 PoE Ports, supporting up to 60W per port<br>12x ports SmartRate 1G/2.5G/5G BaseT Class 6 PoE ports supporting up to 60W per port<br>4x 1G/10G SFP ports (2x LRM 2x LRM/MACSec 256)<br>Supports PoE Standards IEEE 802.3af, 802.3at, 802.3bt (up to 60W)<br>1x RJ-45 Console Port 1x USB-C Console Port 1x OOBM 1x USB Type-A Host port.          |
| Ports                      | 36x ports 10/100/1000BASE-T Class 6 PoE Ports, supporting up to 60W per port<br>12x ports SmartRate 1G/2.5G/5G BaseT Class 6 PoE ports supporting up to 60W per port<br>4x 1G/10G SFP ports (2x LRM; 2x LRM/MACSec 256)<br>Supports PoE Standards IEEE 802.3af, 802.3at, 802.3bt (up to 60W)<br>1x RJ-45 Console Port<br>1x USB-C Console Port<br>1x OOBM<br>1x USB Type-A Host port |
| Memory and processor       | CPU: Quad Core ARM Cortex™ A72 at 1.8 GHz<br>Memory and Flash: 8 GB DDR4 16 GB eMMC                                                                                                                                                                                                                                                                                                  |
| Latency                    | 1 Gbps: 2.28 μSec<br>10 Gbps: 1.46 μSec                                                                                                                                                                                                                                                                                                                                              |
| Throughput                 | Up to 130.9 Mpps                                                                                                                                                                                                                                                                                                                                                                     |
| Routing/switching capacity | 272 Gbps                                                                                                                                                                                                                                                                                                                                                                             |
| PoE capability             | 1440W                                                                                                                                                                                                                                                                                                                                                                                |
| Stacking capabilities      | 8 members                                                                                                                                                                                                                                                                                                                                                                            |
| Power supply name          | 2 field-replaceable, hotswappable power supply slots<br>1 minimum power supply required (ordered separately)<br>Supported PSUs<br>JL086A<br>JL087A<br>Max PoE Power: 1440W                                                                                                                                                                                                           |
| Input voltage              | 100V-120V/200V-240V                                                                                                                                                                                                                                                                                                                                                                  |
| Power consumption          | 76W at 230 VAC                                                                                                                                                                                                                                                                                                                                                                       |
| Product dimensions         | 4.39 x 44.247 x 38.38 cm                                                                                                                                                                                                                                                                                                                                                             |
| Weight                     | 6.01 kg                                                                                                                                                                                                                                                                                                                                                                              |



For additional technical information, available models and options, please reference the [QuickSpecs](#)

## HPE Aruba Networking Services

HPE Aruba Networking services simplify and accelerate the network technology lifecycle, enabling your network to scale with better predictability and cost-effectiveness. Whether you operate your own network and need to improve your IT efficiencies, or you want to offload some of the burden, we have the services you need to reach your goals.

Learn more about what HPE Services - Aruba Networking has to offer at: <https://www.hpe.com/edge/services>

### Support Services

Our support portfolio provides the essential support elements as well as proactive and preventive features to help you improve your team's productivity and get the most from your network. Our support customers benefit from faster issue resolution, simplified operations and efficiencies, and reduced network issues.

### Professional Services

With deep intellectual capital and purpose-built tools, our team delivers a range of standard and custom professional services designed to accelerate your value from HPE Aruba Networking technology.

#### Project based services include:    Annual subscription services include:

- Planning, audit, and assessment
- Architecture review and design
- Deployment, migration, and knowledge transfer
- Network optimization
- Intelligent Operations
- Customer Experience Management

Our [Education Services](#) allow your team to come up to speed quickly.

### HPE GreenLake for Networking

Our NaaS solution, is part of the HPE GreenLake services family, and simplifies network operations, accelerates equipment handling, and increases the value of your HPE Aruba Networking solution. If you need expert guidance and automation-based operations for your team, please explore our NaaS approach through HPE GreenLake for Networking.

Make the right purchase decision.  
Contact our presales specialists.

Visit [HPE.com](https://www.hpe.com)



Contact us